CC1400C VI

Light Tandem Rollers



DYNAPAC
FAYAT GROUP

TECHNICAL DATA

Technical data

Hydraulic system

Driving	Axial Piston Pump with variable displacement. Radial Piston Motors with constant displacemnet
Parking/emergency brake	Failsafe multidisc brake in drum and wheel motors.
Service brake	Hydrostatic in forward and reverse lever.
Steering	Gear pump with constant displacement.

Drum

Drum width	54 in
Split drums	No

Fluids

Emulsion tank, volume	7 US gal
Fuel tank	16 US gal
Hydraulic tank	11 US gal
Hydraulic, oil in system	12 US gal

Weights

Front module weight	4,586 lb
Max operating weight	10,582 lb
Rear module weight	4,012 lb

Standards and certifications

Guaranteed Sound power level, LwA	104 dB

Tyre

Number of tyres	4

Offset

Off-set	2 in

Drive

Speed, transport	6 mph

Speed

Speed, working	2 mph

Compaction

Static linear load, front	13 lb/in

Steering

Steering Angle	43 °
Turning Radius, inside	118 in
Turning Radius, outside	172 in

Traction

Vertical oscillation	10 °

Spray system

Water tank volume	79 US gal

Engine

Emission	Stage IIIA/Tier 3
Manufacturer	Kubota
Model	V2203-M-E3B
Rated power	35 kW (47 hp @ 2700 rpm)
Rated power according to standard	SAE J1995
Type	Water cooled diesel

Engine

Emission	Stage IIIB/Tier 4
Manufacturer	Kubota
Model	V2403-CR-E4B
Rated power	37 kW (50 hp) @ 2,700 rpm
Rated power according to standard	SAE J1995
Type	Water cooled diesel


Engine

Emission	Stage V
Manufacturer	Kubota
Model	V2403-CR E5B
Rated power	37 kW (50 hp) @ 2,700 rpm
Rated power according to standard	SAE J1995
Type	Water cooled diesel

Dimensions


SIDE VIEW

A	78 in	Wheelbase
C	27 in	Curb Clearance
D	35 in	Drum Diameter
H1	112 in	Height, ROPS
H2	80 in	Height, folded ROPS
K	7 in	Ground clearance
L	111 in	Length
S	1 in	Drum shell thickness



TOP VIEW

K	59 in	Width
B3	2 in	Off-set
O1	2 in	Overhang, right
O2	2 in	Overhang, left
R1	172 in	Turning Radius, outside
R2	118 in	Turning Radius, inside
W1	54 in	Drum width
W2	50 in	Width, wheel module
α	43 °	Steering Angle



Questions?

We're happy to help

Find your closest dealer at dynapac.com

