CC4000C VI

Heavy Tandem Rollers - Articulated



DYNAPAC
FAYAT GROUP

TECHNICAL DATA

Technical data

Compaction

Centrifugal force, high amplitude	100 kN
Centrifugal force, high amplitude	113 kN
Centrifugal force, low amplitude	61 kN
Centrifugal force, low amplitude	74 kN
Nominal amplitude, High	0.8 mm
Nominal amplitude, Low	0.3 mm
Static linear load, front	28.9 kg/cm
Vibration, high amplitude	51 Hz
Vibration, low amplitude	67 Hz

Hydraulic system

Driving	Axial piston pump with variable displacement. Radial piston motors (3) with variable displacement.
Parking/emergency brake	Failsafe multidisc brake in drum and wheel motors.
Service brake	Hydrostatic in forward and reverse lever.
Steering	Gear pump with constant displacement

Drum

Drum width	1,680 mm
Split drums	No

Weights

Front module weight	4,850 kg
Max operating weight	9,360 kg
Rear module weight	4,350 kg

Fluids

Fuel tank	180 l
Hydraulic, oil in system	74 l

Standards and certifications

Guaranteed Sound power level, LwA	108 dB

Offset

Off-set	520 mm

Drive

Speed, transport	12 km/h

Speed

Speed, working	6 km/h

Steering

Steering Angle	32 °
Turning Radius, inside	5,590 mm
Turning Radius, outside	7,270 mm

Traction

Vertical oscillation	7 °

Spray system

Water tank volume	680 l

Dimension Machine

Working width	1,680 mm

Engine

Emission	Stage IIIA/Tier 3
Manufacturer	Cummins
Model	QSF 3.8
Rated power	104 kW (140 hp) @ 2200 rpm
Rated power according to standard	SAE J1995
Type	Water cooled turbo diesel


Engine

Emission	Stage V/Tier 4f
Manufacturer	Cummins
Model	F3.8
Rated power	100 kW (135 hp) @ 2,200 rpm
Rated power according to standard	SAE J1995
Type	Water cooled turbo diesel

Dimensions


SIDE VIEW

A	3,720 mm	Wheelbase
C	810 mm	Curb Clearance
D	1,220 mm	Drum Diameter
H	2,990 mm	Height
K	310 mm	Ground clearance
L	4,915 mm	Length
S	18 mm	Drum shell thickness



TOP VIEW

O	520 mm	Off-set
R1	7,270 mm	Turning Radius, outside
R2	5,590 mm	Turning Radius, inside
W1	1,680 mm	Drum width
α	32 °	Steering Angle



Questions?

We're happy to help

Find your closest dealer at dynapac.com

